# **O** Documentation

Release 2.0

Phase

November 16, 2015

#### Contents

1	<b>1. G</b> 1.1 1.2	etting Started         1.1. Getting the interpreter       1.1. Getting the interpreter         1.2. Let's test it out!       1.1. Getting the interpreter
•		
2	2. TI	he Basics
2	<b>2. T</b> 2.1	he Basics 2.1. I/O
2	<b>2. T</b> 2.1 2.2	he Basics         2.1. I/O         2.2. Number Literals are pushes individually

The O Language is an esoteric programming language used for code-golf. You can try it online at https://o-lang.herokuapp.com.

Docs:

#### 1. Getting Started

Getting started in O is easy! Just follow the steps below and you'll be ready to go!

#### 1.1 1.1. Getting the interpreter

You can download latest release from http://github.com/phase/o/releases or clone the repository and compile it manually:

```
git clone https://github.com/phase/o && cd o
gcc o.c -o o
./o
```

Running the executable without any arguments will open the REPL, which you can type lines of O code into to have them interpreted.

You can also go to http://o-lang.herokuapp.com and use the always-updated-interpreter so you won't have to recompile every update.

### 1.2 1.2. Let's test it out!

Whether you're on the online IDE or using the REPL, this Hello World program will run on both:

"Hello, World!"o

This is the simplest *Hello World* program in O. It pushes the string Hello, World! to the stack and outputs it with o. You will learn about why the o isn't needed in the next section.

### 2. The Basics

O revolves around one stack in which you can push and pop values to and from. Here are some basic rules for writing O code.

#### 2.1 2.1. I/O

There are a couple ways to get a user's input. i will push the input to the stack as a string, while j will push the input to the stack as an integer.  $\circ$  pops the top value off the stack and outputs it. p outputs with a new line. Here's an example:

>>> io test test

This is the smallest cat program possible. i gets the input and pushes it, o pops it and outputs it to stdout.

Another cool feature of O is that the stack contents will pe outputted when the code finishes execution. Meaning "1234" will output "1234", while "12340000" will output "4321". This feature does not work in the REPL.

#### 2.2 2.2. Number Literals are pushes individually

1234 doesn't push the number *one thousand twenty-four*, it pushes 1, then 2, 3, and finally 4. Each individual digit is pushed to the stack:

```
>>> 12340000
4321
```

Each o pops one number off and outputs it, meaning the number that was pushed last will pop off first.

#### 2.2.1 2.2.1. Hexadecimal works too

Hexadecimal numbers work for capital notation. Lowercase notation is saved for other functions.

>>1Aoo 101

1 was pushed to the stack, then A pushed 10 to the stack, and then they were outputted.

## 2.3 2.3. Strings are enclosed in quotes

To make a string, you just need to enclose it within quotes.

```
>>> "Hello, World!"o
Hello, World!
```

What about printing something different?

```
>>> "Hello'World!"oo
World!Hello
```

#### 2.3.1 2.3.1 Strings don't need quotes

Remember when I said you need to put them in quotes? I lied. ' has some interesting properties with strings. When used by itself, it will push the next character to the stack as a string.

>>> 'ao a

If you are in the middle of making a string, it will push the current string buffer to the stack and start making a new string (like a macro for "").

```
>>> "a'a"oo
aa
>>> "hello'madam"oo
madamhello
```